UNITRAC STOU 10W-40

Multifunktionalöl für Traktoren.
Multifunctional Super Tractor Oil Universal.
Višenamjensko univerzalno Super Traktor ulje.

UNITRAC STOU 10W-40

STOU (Super Tractor Oil Universal) Multifunktionalöl, das den Empfehlungen namhafter Traktorenhersteller gerecht wird. Einer der Vorteile ist die universelle Anwendbarkeit in Motoren, Getrieben, Hydrauliksystemen, nassen Bremsen und Endantrieb von allen modernen Traktoren. Hochwertige Basisöle und moderne Additive gewährleisten einen störungsfreien Betrieb aller Aggregate zu jeder Jahreszeit.

UNITRAC STOU 10W-40

Multifunctional STOU (Super Tractor Oil Universal) lubrication oil designed for all types of agricultural machinery with a common lubricating system for the engine, transmission, hydraulic, wet clutches and brakes. It is specially formulated for lubricating the mechanical system of farm tractors, combine harvesters, silo loaders, equipment and vehicles with diesel engines (whether supercharged or not) and conventional mechanical transmissions.

UNITRAC STOU 10W-40

MIDLAND „STOU“ (Super Tractor Oil Universal) ulje za podmazivanje svih vrsta poljoprivrednih strojeva sa zajedničkim sustavom podmazivanja motora, transmisije, hidraulike, mokrih spojki i kočnica. To je posebno formulirano ulje za podmazivanje mehaničkih sustava poljoprivrednih traktora, kombajna, šila na kotačima, razne opreme i vozila s dizel motorima (sa turbo i bez turbo motorima) i konvencionalnih mehaničkih prijenosnika.

Midland®
Swiss Quality Oil.

DE **Eigenschaften und Vorteile**

- ausgezeichnetes Viskositäts-Temperaturverhalten
- hervorragende Detergent- und Dispergiereigenschaften
- beste Kaltstarteigenschaften
- hohe Alterungsstabilität
- universeller Einsatzbereich

EN **Benefits**

- excellent properties in all climates and service conditions
- excellent detergent-dispersant capacity keeps the engine clean
- optimal viscosity at all temperatures and fluidity at low temperatures
- antifoam and deaeration capabilities
- extreme pressure characteristics – suitable for transmissions, where API GL-4 is recommended
- protection against wear and corrosion
- compatible with other lubricants of same type
- oxidation resistance and anti-friction properties to prevent noise in multidisc clutches
- suitable for wet clutches and brakes

HR **Prednosti**

- izvrsna svojstva u svim klimatskim uvjetima i otežanim uvjetima rada
- izvrsna sposobnost održavanja motora čistim
- Optimalna viskoznost pri svim temperaturama i fluidnost pri niskim temperaturama
- sprječavanje stvaranja pjene i ozračivanje sistema
- izvrsna svojstva kod velikih opterečenja - pogodne za mjenjače, gdje se preporučuje API GL-4
- štiti od trošenja i korozije
- kompatibilan s drugim mazivima istog tipa
- otporno na oksidacija i svojstvo anti-trenja kako bi se spriječilo stvaranje u multi disk spojkama
- pogodan za mokre spojke i kočnice

	Packungseinheiten	Packaging	Pakiranje
	1/1 Fass zu 180 kg (ca. 209 L)	Drum of 180 kg (ca. 209 L)	Bačva od 180 kg (ca 209 L)
	1/4 Fass zu 54 kg (ca. 63 L)	Drum of 54 kg (ca. 63 L)	Bačva od 54 kg (ca. 63 L)

Artikel-No | Product Code | Šifra artikla	**22721**	**Version 2019-07**

Typische Analysedaten	Typical Properties	Karakteristična svojstva	
Viskosität cSt bei 40°C	Viscosity cSt @ 40°C	Viskoznosti cSt @ 40°C	91.36
Viskosität cSt bei 100°C	Viscosity cSt @ 100°C	Viskoznosti cSt @ 100°C	14.44
Viskositätsindex (VI)	Viscosity Index (VI)	Indeks viskoznosti (IV)	164
Stockpunkt °C	Pour Point °C	Tecište °C	-33
Flammpunkt °C	Flash Point °C	Plamište °C	221
Spez.Gewicht kg/L	Gravity kg/L	Specifična težina kg/L	0.861

Spezifikationen | Features | Specifikacije

ACEA E2 • Allison C-4 • API CG-4/SF, GL-4 • Caterpillar TO-2 • Ford M2C 159C • John Deere J27
Massey Ferguson CMS M 1135, M 1139, M 1144, M 1145 • ZF TE-ML 06B, 06C, 06D, 06F, 06Q, 06R, 07B

oelbrack®
Midland – eine Marke der Oel-Brack AG.
www.oelbrack.ch