

STRUB Pipe Thread Sealing Compound H1

Food Grade per USDA 21 CFR 178.3570

Article number 31426



Opis

STRUB Pipe Thread Sealing Compound H1 je dobroprijanjajuća i lako razmazujuća pasta sa dobrim svojstvima protiv korozije (ne izaziva koroziju prema EN-ISO 2160 on Al, Cu, Zn-alloys, steel, zinc). Vijci se lako otpuštaju nakon prijene ove paste.

Primjena

Pasta za brtvljenje koja se ne ukružuje u kombinaciji sa konopljom za vodoinstalaterske, plinske, područja hrane, prskalice, vodene sisteme i sl.

Prednosti

- ✓ Otporna na starenje
- ✓ Dobra stabilnost od oksidacije pri visokim temperaturama
- ✓ (Pad pritiska nakon 100h/ 50°C max. 0.2 bar)
- ✓ Dobra vodootpornost
- ✓ Otpornost na ekstremne cikluse temperature
- ✓ Pasta je otporna na plin i plinske kondenzante(nije primjerena za ukapljeni plin)
- ✓ Otporna na hidrokarbon plinove(methane, acetylene, ethylene), hydrogen, nitrogen, carbon monoxide, carbon dioxide, water vapour, inert gases, and dilute and gaseous ammonia
- ✓ Pasta je bez silikona stoga neće prouzrokovati pucanje PE i PVC cijevi
- ✓ Nema ošpasnosti od vode

Karakteristična svojstva

Colour	visual	light grey
Structure		good adherent
NLGI-Class		2
Drop point	°C	none
Application Temperature	°C	- 25°C up to + 200°C

Transport

ADR/SDR: Nije opsano

Ključni broj otpada

LVA VeVA / EAK: 12 01 12

The information contained in this technical data sheet are based on the general knowledge and application possibilities. Strub + Co. AG is not liable for damage resulting from improper use of the products. The industry-standard measurement and production tolerances apply to the specified characteristics. Generally, no legally binding can be derived from this data. Our products are constantly further developed. Therefore Strub + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.