

STRUB Erodfluid

200, 220, 235, 239

Electrical discharge machining (EDM) fluid
Catalytic cracking fluid



Opis

STRUB Erodfluid je nisko viskozna, katalitička sintetizirana tekućina za obradu električnog otpada za sve razine performansi.

Primjena

Erodfluid 235 + 239 su ulja nešto veće viskoznosti od 200 i 220 i gradacije koja se mogu koristiti u strojevima svih veličina. Priprema se za optimalnu brzinu uklanjanja metala i nisku potrošnju elektroda.

Erodfluid 200 + 220 formulirani su inovativnom tehnologijom bazne tekućine koja odgovara svjećicama strojeva svih snaga i veličina. Erodfluid 200 + 220 su vrhunske kvalitete, višenamjenski dielektrični fluidi, dizajnirani da omogućе optimalne brzine uklanjanja metala, zajedno s niskim trošenjem elektroda, dobrom površinskom završnom obradom i fine tolerancije.

Prednosti

- ✓ Otporan na oksidaciju, za duži vijek trajanja
- ✓ Visoka sposobnost uklanjanja metala i niska potrošnja elektroda
- ✓ Izvrsno hlađenje, ispiranje i filtriranje
- ✓ Visokorafinirana ulja bez aromatičnih dodataka za sigurno radno okruženje
- ✓ Nisko generiranje dima i mirisa

Tehnički podatke

STRUB Erodfluid		200*	220*	235**	239**
Art.-Nr.		31441	31442	31465	30384
Colour		Yellow, clear	Yellow, clear	Yellow, clear	Yellow, clear
Density at 20°C	g/cm ³	0.775	0.780	0.810	0.815
Viscosity at 20°C	mm ² /s	2.9	3.3	3.8	4.3
Viscosity at 40°C	mm ² /s	2.0	2.2	2.5	2.8
Flash Point	°C	102	104	108	108
Pour Point	°C	< - 10	< - 10	< - 40	< - 40

Transport

ADR/SDR:

Nije opasno

Ključni broj otpada

LVA Veva / EAK:

12 01 07

The information contained in this technical data sheet are based on the general knowledge and application possibilities. Strub + Co. AG is not liable for damage resulting from improper use of the products. The industry-standard measurement and production tolerances apply to the specified characteristics. Generally, no legally binding can be derived from this data. Our products are constantly further developed. Therefore Strub + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.

STRUB + Co. AG
 Swiss Tribology

Mühlemattstrasse 5
 CH-6260 Reiden

phone +41 62 785 22 22
 fax +41 62 785 22 33

strub@strub-lube.ch
 www.strub-lube.ch